HK INSTRUMENTS

DIFFERENTIAL PRESSURE GAUGES AND MANOMETERS MMU SERIES

U-tube manometer for HVAC applications

Traditional U-tube manometer with easy zero point calibration.

Liquid column manometers are reliable and inexpensive traditional pressure meters. The manometers are good for measuring and indicating small overpressure, underpressure and differential pressure of air and non-aggressive gases in low pressure ranges.







SIMILAR PRODUCTS

- DPG series differential pressure gauges
- MM series inclined column manometers

APPLICATIONS

Liquid column manometers are ideal for general-purpose work in air-conditioning and ventilation, monitoring of air filters for contamination and monitoring of airflow and air velocity.

MODEL SUMMARY

Description	Model Product cod	Measurement range (Pa)
U-tube manometer	MMU±500 113.002.00	±500

DIFFERENTIAL PRESSURE GAUGES AND MANOMETERS MMU SERIES

SPECIFICATIONS

Performance

Accuracy: 10 Pa Overpressure: Max pressure 500 Pa

Technical specifications

Measuring units: Pa Measuring ranges: ±500 Pa Environment: Operating temperature: 40...+60 °C Gauge fluid: Red: s.g. 0.786 kg/dm (15 °C) (Isopar M)

Physical

Dimensions: Height: 190 mm Width: 45 mm Mounting position: vertical Case: ABS Cover: PC Locking screw: Brass/Steel Weight: 55 g without fluid

Conformance

Meets the requirements for CE marking: RoHS Directive: 2011/65/EU

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED BY DNV GL = ISO 9001 = ISO 14001 =



PRC Technologies Corp., Ltd. Tel: 02 530 1714, 02 530 1619, 02 530 1621 Fax: 02 530 1731 Email: info@prctechth.com, www.prctechth.com